



**Body Armor 4x4 by Tolar Mfg.**  
258 Mariah Circle, Corona CA 92879  
Ph: 951-808-0750  
Customer service hours:  
8am to 4 PM Pacific Time  
[www.bodyarmor4x4.com](http://www.bodyarmor4x4.com)

**Installation instructions for JK-2961**  
**Fits 2007- Current Jeep Wrangler JK, all models**

- \*\* Inspect bumper and swing arm prior to installation. Contact us at 951-808-0750 if missing parts
- \*\* Due to the weight of the bumper it is recommended at least two people for installation
- \*\* This is a stock replacment bumper, it is not designed to carry a swing arm tire carrier

**Hardware List:**

Bumper Qty: 1
16MM-50MM Hex Head Bolt Qty: 4
16MM Flat washer Qty: 4
16MM Lock Washer Qty: 4
Inside frame brackets Qty: 2

**Removing Factory Bumper:**

- Step 1 Remove the factory rear bumper.
- 2 Insert the nut plates into the inside of the frame rails. They should be positioned to sit on the bottom of the frame with the nuts of the bracket aligning with the large holes on the outside of the frame.
- 3 Place the lower bumper section on the frame and loosely attach using the four 16MM bolts with a lock washer and flat washer. Use the 4 10MM OEM bolts in the small holes *The 16MM bolt with lock washer and flat washer will insert through the bumper bracket, through the frame and into the nut plate brackets, tighten all hardware*

