

## 04 - Vehicle Quick Reference / Capacities and Recommended Fluids / Specifications

**SPECIFICATIONS****ENGINE**

Description	Type	Capacities		Part Number	Global Part Number
		U.S.	Metric		
<b>Cooling System</b>					
Engine Coolant (1.8L Turbo Engine)	We recommend you use MOPAR Antifreeze/Coolant 10 Year/150,000 Mile Formula OAT (Organic Additive Technology) or equivalent meeting the requirements of Material Standard MS.90032.	11.2 Quarts	10.6 Liters	68163848AB	68163848GB
<b>Engine Oil with Filter</b>					
Engine Oil (1.8L Turbo Engine)	We recommend you use SAE 5W-40 API Certified Synthetic Engine Oil, meeting the requirements of Material Standard MS-12991.	6.1 Quarts	5.8 Liters	5127394PC	5127394PC
Engine Oil Filter (1.8L Turbo Engine)	We recommend you use MOPAR® Engine Oil Filter.	N/A	N/A	—	—
<b>Fuel (approximate)</b>					
Fuel Selection (1.8L Turbo Engine)	Use Only 91 Octane or higher, 0-10% Ethanol.	10.5 Gallons	40 Liters	—	—
Reserve Fuel	—	1.1 Gallons	4 Liters	—	—
<b>A/C Refrigerant System</b>					
Refrigerant	R-1234yf	0.815 Pounds	0.370 ± 0.02 Kilograms	68224028AB	68224028GA
Oil	Idemitsu PS-D1	4.2 Ounces	120 [cc]	—	—

**SPARK PLUGS**

Description	Type	Gap	

		U.S.	Metric
Spark Plugs (1.8L Turbo Engine)	We recommend you use MOPAR® Spark Plugs. *	0.024 in	0.6 mm
<p>* The following are essential to ensure correct operation and prevent serious damage to the engine: only use spark plugs of the same make and type which are specially certified for such engines strictly comply with the spark plug replacement interval given in the maintenance schedule. For spark plug replacement, it is advisable to contact the dedicated Alfa Romeo Dealership. Refer to the "Maintenance Schedule" section for the required spark plug intervals.</p>			

## TRANSAXLE

Description	Type	Capacities		Part Number	Global Part Number
		U.S.	Metric		
Alfa Twin Clutch Transmission	Gearbox: Full synthetic 75W-85 manual transmission fluid meeting MS.90030-M2 and the API GL4 specification.	2.0 Quarts	1.88 Liters	68092630AA	68092630GA
	Control System: Use only MOPAR C Series DDCT SAE 75W Hydraulic Fluid or equivalent. Failure to use the correct fluid may affect the function or performance of your transmission.	1.5 Quarts	1.45 Liters	68092638AB	68092638GA

## CHASSIS

Description	Type	Capacities		Part Number	Global Part Number
		U.S.	Metric		
Brake Master Cylinder	We recommend you use MOPAR® DOT 4. If DOT 4 brake fluid is not available, then DOT 3 is acceptable.	19.75 Ounces	.56 Kilograms	04549625AD	04549625GD