



PENNZOIL PLATINUM® 5W-30

FULL SYNTHETIC MOTOR OIL WITH PUREPLUS™ TECHNOLOGY

TECHNICAL DATA SHEET

Pennzoil Platinum® with PurePlus™ Technology is a first of its kind full synthetic motor oil made from natural gas and designed for COMPLETE PROTECTION.

PERFORMANCE, FEATURES & BENEFITS

PurePlus™ Technology is our patented, revolutionary gas-to-liquid process that converts natural gas to first-of-its-kind extremely high quality full synthetic base oil.

Because our base stock is made from natural gas, it is crystal clear with fewer of the impurities found in crude oil, the start for many other traditional & synthetic motor oils.

From that pure, clear base we add our unique Active Cleansing Agents to create Pennzoil Platinum, a motor oil designed for COMPLETE PROTECTION without compromise.

• CLEANER PISTONS

Based on Sequence IIIG piston deposit test using SAE 5W-30

• BETTER FUEL ECONOMY

Fuel economy measurements made using CAFÉ cycle under FTP75. Avg of 550 extra miles based on mixed city/highway miles and US avg of 13,476 miles driven per year with 4.1% better MPG vs dirty engine. Source fhwa.dot.gov, 2011.

Follow OEM recommended oil drain intervals.

• PROTECTS HORSEPOWER

• UNSURPASSED WEAR PROTECTION

Based on Sequence IVA wear test using SAE 5W-30

• EXCELLENT PERFORMANCE IN EXTREME TEMPERATURES

MAIN APPLICATIONS

Pennzoil Platinum® 5W-30 Full Synthetic Motor oil with PurePlus™ Technology is recommended for several US and Japanese OEM's including General Motors, Suzuki, Subaru and Nissan.

Often recommended for vehicles with direct injection engines.

Always consult your owner's manual for the correct viscosity choice and specification grade of oil required. Viscosity recommendations often allow a range of viscosities based on local temperatures.

SPECIFICATIONS, APPROVALS & RECOMMENDATIONS

Exceeds the requirements of the following industry specifications:

API SN and all previous categories

- ILSAC GF-5 and ACEA A1/B1
- A5/B5
- Exceeds Chrysler MS-6395, Ford WSS-M2C946-A, GM 6094M, GM 4718M, Honda/Acura HTO-06 and dexos1®

TYPICAL PHYSICAL CHARACTERISTICS

Properties		Method	Pennzoil Platinum®	
SAE Viscosity Grade		SAE J300	5W-30	
API Service Category			SN	
ILSAC			GF-5	
ACEA			N/A	
Density	g/cm ³	ASTM D4052	0.84	
Flash Point	°C	ASTM D93	224	
Pour Point	°C	ASTM D97	-48	
Kinematic Viscosity	@ 40°C	cSt	ASTM D445	56.9
Kinematic Viscosity	@ 100°C	cSt	ASTM D445	10.3

Properties			Method	Pennzoil Platinum®
Viscosity Index			ASTM D2270	170
CCS Viscosity	@-30°C	cP	ASTM D5293	4 000
MRV Viscosity	@-35°C	cP	ASTM D4684	10 500
Noack Volatility		%	ASTM D5800	10.1

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

Pennzoil Platinum Full Synthetic Motor Oil is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil.
After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet (MSDS), which can be obtained from www.epc.shell.com

Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

ADDITIONAL INFORMATION

Advice

To find the right Pennzoil product for your vehicles and equipment, please consult www.pennzoil.com to look-up the right motor oil recommendation using our oil selector.

Advice on applications not covered here may be obtained from your Shell representative.