



## ATF +4

Castrol Transmax™ ATF+4® Automatic Transmission Fluid

### Description

Castrol Transmax™ ATF+4® Automatic Transmission Fluid is for use in Chrysler vehicles.

### Advantages

- Full synthetic formula exceeds ATF+3® requirements
- Technologically advanced, full synthetic formulation provides superior transmission life
- Engineered with superior base oils to ensure superb low and high temperature performance
- Certified and approved for all Chrysler cars and trucks that require ATF+4®, ATF+3®, ATF+2®, ATF+2 Type 7176® or ATF+®

### Warranty and Protection Requirements

- Exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles, transmissions or power steering service where a ATF+4®, ATF+3®, ATF+2®, ATF+2 Type 7176® or ATF+® is specified.

### Industry Specifications and OEM Approvals

- Meets or Exceeds Chrysler ATF+4® Requirements
- ATF+4® approved and licensed by Chrysler Group LLC (License number 40630033)

## Typical Characteristics

Name	Method	Units	AFF +4
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	33
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	7.5
Viscosity Index	ASTM D2270		206
Color, Typical	ASTM D1500		7
Appearance	Visual		Red
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	8,500
Pour Point	ASTM D97	°C (°F)	-51 (-60)
Flash Point	ASTM D92	°C (°F)	195 (383)
Specific Gravity, 60°F	ASTM D1298		0.85
Pounds per Gallon	ASTM 287		7.08

## Storage

Please store the product in a container out of direct sunlight etc.